Panasonic



KX-HDV130

FLEXIBLE FEATURES FOR COST-CONSCIOUS BUSINESSES

The Panasonic KX-HDV130 IP deskphone delivers the ideal balance of low cost/high quality, alongside a range of value-adding features.

Designed to suit business buyers who demand budget-friendly technology that provides the reliable, flexible performance their businesses require, the KX-HDV130 makes professional-grade communications more accessible than ever.

Key Features

- 2-line SIP phone
- HD sound with wideband audio
- Full-Duplex speaker phone
- Support for UC features including Broadsoft UC-ONE, uaCTSA
- 2 x SIP accounts
- 2 x LAN ports

PRODUCT GUIDE AND SPECIFICATIONS



KX-HDV130 (Display)



KX-HDV130 (White)



KX-HDV130 (Black)

* Please note that the above images are the NE version. There is also an X version which uses characters instead of pictograms.

Total based
Touch panel COD Set Ashing No COD Set Ashing No COD Set Ashing No Code Ashing No Code Ashing No Code Ashing No Response No No No No No No No No
COD Section No. Yes Technology Yes Yes Technology Yes
COD Backshipht Yes No Control Floring No Control Floring No Control Floring No Control Floring Pages No Control Floring Pages Pa
Collabeling Pages No
Manage Wating & Ringer indicator 1 cotour (Blue)
Message Waiting & Ringer Indicator 1 cotion (Blue)
REVI Soft Key 3 Plesible function & Line Indicator 2 colours (Blore / Red.) Soft Key 3 Plesible function & Line Indicator 2 Page Key No No Soft Key 4 Page Key No No Soft Key 5 Office A Key 5 Walline Key 7 Volume Key 8 Si (Cancel, Conference, Transfer, Hold/Message, Redoil, Multi-Alato Asswer, SP-Phone, Neadosci) Network Interface 2 x 8.45 to 1/100 base-1 (Antol 1 1000-8-844E f 1000-8-144E) Auto MID/ MI Risostor Full Duplex Wilschand Houring aid compatibility Wired Flacebet port 8 Wired Flacebet port 1 Yes Full Duplex Right Poul 4 Risostori port) No No Sills Forces port No No Sills Forces port) No No Sills Forces port Sills Forces port No No Sills Forces port Sills Forces port No Sills Forces port Sills Forces port No No Sills Forces port No No Sills Forces p
Soft Key 3 3 Flexible function & Line Indicator 2 Page Key No S (up/downlet fr inpAtEnter) Nov. Keys S (up/downlet fr inpAtEnter) Nov. Keys S (up/downlet fr inpAtEnter) Nov. Keys Yes Yes Valume Key Yes Yes Valume Key Yes Yes Valume Key S (Cancel, Conference, Transfer, Hold/Message, Reads, Holf / Note Authorition Ancience, S 2 x R.45 10 / 100 boses / (Anto 1 100M S-FULL, 1 100M S-HALF) And Novel / Message Handstel
Soft Key 3 2 2 2 2 2 2 2 2 2
Flexible function & Line Indicator 2
Page Key No S (up/dom/litty right/Enter)
Navi Keys S (up/down/lett/right/Enter)
Yes
Volume Key Yes (-/-)
Bedracated Keys
Network Interface
Network Interface
Handset Full Duplex Wideband Hearing aid compatibility Wired Headset port Yes Full Duplex (RJ9 jack) Elis (central port) No Builtin Bluetooth No Expansion module (DSS) Wild support Expansion module (DSS) maximum install No Expansion module (DSS) Interface No SPPhone Yes Wirdeband Full Duplex (EEE 1329 compatible) USS Interface No Ringer Tone 32 ECO mode (LAK) speed: 10Mbps only; Cannot use 2nd port Poel Calass Class 1 CLoss 1 CLosu Wall mount High position: 167 x 173 x 115 (excluding handset) Low position: 167 x 173 x 115 (excluding handset) Electric Volume Specification SPPhone 8 levels Ringer Ringer Ringer Ringer Ringer Ringer LOD Contast LOD backlight Ringer LOD backlight mode On/Auto/Off
Wired Headset port Yes Full Duplex (R.19 jack) EHS (rote port) No EHS (voic port) No Builti Bluetouth No Expansion modula (DSS) Expansion modula (DSS) maximum install Expansion Module (DSS) maximum install Expansion Module (DSS) Interface No SPPhone Yes Wirdeband Full Duplex (IEEE 1329 compatible) USB interface No Ringer Tone SPPhone SPOVER Supply AC Adaptor, PoE (IEEE 802 3at) Poet Class Class 1 AC adapter Yes (Optional) KX-A423 Installation Desk stand (Angle) Wall mount Desk stand (Angle) Wall mount Demension (Wx D x H mm) High position: 167 x 165 x 148 (excluding handset) Low position: 167 x 173 x 115 (excluding handset) Electric Volume Specification SPPhone Reset Service Ringer Reset Service Ringer Reset Service Rese
EHS (control port) RIS (voice port) No Builtin Bluetoeth No Expansion module (DSS) Expansion module (DSS) Interface No Expansion Module (DSS) Interface No SPPhone Yes Wideband Full Duplex (IEEE 1229 compatible) USB interface No Ringer Tone Condow (LAN speech 10Mbps only; Cannot use 2nd port Yes Prover Supply AC Adaptor, Pet (IEEE 802.3af) Pot Yes Crass Class 1 Ac despiter Yes (optional) KX-A423 Installation Desk stand (Angle) Desk stand (Angle) Ves (optional) Wall mount Dimension (Wx D x H mm) High position: 167 x 163 x 148 (excluding handset) Colour Electric Volume Specification SPPhone 8 Levels Ringer Ringer Ringer Ringer Ringer Ringer Ringer LOD Contrast LCD Backlight AC develop (IEEE 802.3af) Rod Rod Rod Rod Rod Rod Rod Ro
Billin Bluetnoth No Expansion module (DSS) Expansion module (DSS) maximum install Expansion Module (DSS) Interface SPPhone SPPhone Yes Wideband Full Duplex (IEEE 1379 compatible) USB interface No Ringer Tone CECO mode (LAN speed: 10Mps only; Cannot use 2nd port Power Supply AC Adaptor, PoE (IEEE 802.3af) PoE PoE (Power of Expansion Module) Class 1 AC adapter Yes (potional) KX-A423 Installation Desk stand (Angle) Desk stand (Angle) Desk stand (Angle) Wall mount Yes (optional) Will mount Will mount Will mount Milgh position: 167 x 165 x 148 (excluding handset) Colour White Black Electric Volume Specification SPPhone A levels - Off A levels - Off A lour on the stand in the stands Ringer A levels - Off LLO Contrast LCD Backlight mode On/Auto/Off
Builtin Bluetooth No Expansion module (DSS) Not support Expansion module (DSS) maximum install No Expansion Module (DSS) Interface No SPPhone Yes Wideband Full Duplex (IEEE 1329 compatible) USB interface No Ringer Tone 32 ECO mode (LAN speed: 10Mbps only: Cannot use 2nd port Yes Power Supply AC Adaptor, PoE (IEEE 802.3af) Poe (Power of Expansion Module) . PoE (Power of Expansion Module) . PoE (ass) Class 1 AC adapter Yes (optional) KX-A423 Installation Yes (optional) KX-A423 Installation Yes (optional) KX-A423 Desk stand (Angle) 2 position (30/45) Wall mount Yes (option) Dimension (W x D x H mm) High position: 167 x 173 x 115 (excluding handset) Colour White/ Black Electric Volume Specification Runger Electric Volume Specification 8 levels Ranger B levels LOD Docktight 5 levels LOD Docktight </td
Expansion module (DSS) Not support Expansion module (DSS) Interface No SPPhone Yes Wideband Full Duplex (IEEE 1329 compatible) USB interface No Ringer Tone 32 ECO mode (LAN speed: 10Mbps only; Cannot use 2nd port Yes Power Supply AC Adaptor, PoE (IEEE 802.3af) PoE Yes PoE (Power of Expansion Module) . PoE (class) Class 1 AC adapter Yes (optional) KX-A423 Installation Yes (optional) KX-A423 Wall mount Yes (optional) Dimension (W x D x H mm) High position: 167 x 165 x 148 (excluding handset) Colour White/ Black Electric Volume Specification 8 levels SPPhone 8 levels Handset 8 levels Ringer 8 levels Ringer 8 levels LCD Contrast 6 levels LCD backlight mode 0 n/Auto/Off
Expansion module (DSS) maximum install No Expansion Module (DSS) Interface No SPPhone Yes Wideband Full Duptex (IEEE 1329 compatible) USB interface No Ringer Tone 32 ECC Umode (LAN speed: 10Mbps only; Cannot use 2nd port Yes Power Supply AC Adaptor, PoE (IEEE 802.3af) PoE Yes PoE (Power of Expansion Module) - PoE class Class 1 AC adapter Yes (optional) KX-A423 Installation Yes (optional) KX-A423 Installation Yes (optional) KX-A423 Usal mount Yes (option) Usal mount
Expansion Module (DSS) Interface Yes Wideband Full Duplex (IEEE 1329 compatible) USB interface No Ringer Tone 32 ECO mode (LMX speed: 10Mbps only; Cannot use 2nd port Yes Power Supply AC Adaptor, POE (IEEE 802.3ar) PoE Yes POE (Power of Expansion Module) - POE (class Class 1 AC adapter Yes (optional) KX-A423 Installation Yes (optional) KX-A423 Installation Yes (optional) KX-B223 Dimension (W x D x H mm) High position: 167 x 155 x 148 (excluding handset) Colour White/ Black Electric Volume Specification 8 Levels SPPhone 8 Levels Ringer 8 Levels Ringer 8 Levels LCD Contrast 6 Levels LCD Backlight 3 Levels + Off LCD Backlight mode 0 n/Auto/Off
SPPhone Yes Wideband Full Duplex (IEEE 1329 compatible) USB interface No Ringer Tone 32 EECO mode (LAN speed: 10Mbps only; Cannot use 2nd port Yes Power Supply AC Adaptor, PoE (IEEE 802.3af) POE Yes POE (power of Expansion Module) - POE class Class 1 AC adapter Yes (optional) KX-A423 Installation Yes (optional) KX-A423 Mall mount Yes (option) Dimension (W x D x H mm) High position: 167 x 157 x 148 (excluding handset) Colour White/Black Colour White/Black Electric Volume Specification 8 (evels SPPhone 8 (evels Handset 8 (evels Ringer 8 (evels LCD Contrast 6 (evels LCD Contrast 6 (evels LCD Backlight mode 0 (7)Auto/Off
USB interface No Ringer Tone 32 ECO mode (LAN speed: 10Mbps only; Cannot use 2nd port Yes Power Supply AC Adaptor, PoE (IEEE 802.3af) POE Yes PoE (Power of Expansion Module) - POE class Class 1 AC Adapter Yes (optional) KX-A423 Installation Desk stand (Angle) 2 position (30/45) Wall mount Yes (option) Dimension (W x D x H mm) High position: 167 x 165 x 148 (excluding handset) Colour White/Black Electric Volume Specification SPPhone 8 levels Handset 8 levels Ringer 8 levels - Off LCO Contrast 6 levels LCO Backlight mode 0 On/Auto/Off
Ringer Tone 32 CCO mode (LAN speed: 10Mbps only; Cannot use 2nd port Yes Power Supply AC Adaptor, PoE (IEEE 802.3af) PoE Yes PoE (Power of Expansion Module) - PoE class Class 1 AC adapter Yes (optional) KX-A423 Installation Yes (optional) KX-A423 Installation Yes (optional) KX-A423 Installation Yes (optional) KX-BEC (Installation Yes (Installa
Yes Yes
Power Supply AC Adaptor, PoE (IEEE 802.3af) PoE Yes PoE (Power of Expansion Module) - PoE class Class 1 AC adapter Yes (optional) KX-A423 Installation Yes (option) Desk stand (Angle) 2 position (30/45) Wall mount Yes (option) Dimension (W x D x H mm) High position: 167 x 173 x 115 (excluding handset) Colour White/ Black Electric Volume Specification 8 Levels Handset 8 Levels Handset 8 Levels Ringer 8 Levels + Off LCD Contrast 6 Levels LCD Backlight 3 Levels + Off LCD backlight mode 0 n/Auto/Off
Power Supply AC Adaptor, PoE (IEEE 802.3af) PoE Yes PoE (Power of Expansion Module) - PoE class Class 1 AC adapter Yes (optional) KX-A423 Installation Yes (option) Desk stand (Angle) 2 position (30/45) Wall mount Yes (option) Dimension (W x D x H mm) High position: 167 x 173 x 115 (excluding handset) Colour White/ Black Electric Volume Specification 8 Levels Handset 8 Levels Handset 8 Levels Ringer 8 Levels + Off LCD Contrast 6 Levels LCD Backlight 3 Levels + Off LCD backlight mode 0 n/Auto/Off
POE Yes POE (Power of Expansion Module) - POE class Class 1 AC adapter Yes (optional) KX-A423 Installation Poesk stand (Angle) 2 position (30/45) Wall mount Yes (option) Dimension (W x D x H mm) High position: 167 x 165 x 148 (excluding handset) Colour White/ Black Electric Volume Specification 8 Levels Handset 8 Levels Handset 8 Levels Ringer 8 Levels + Off LCD Contrast 6 Levels LCD Backlight 3 Levels + Off LCD backlight mode 0 n/Auto/Off
POE (Power of Expansion Module) - POE class Class 1 AC adapter Yes (optional) KX-A423 Installation Poesk stand (Angle) 2 position (30/45) Wall mount Yes (option) Dimension (W x D x H mm) High position: 167 x 165 x 148 (excluding handset) Colour White/ Black Electric Volume Specification 8 Levels Handset 8 Levels Ringer 8 Levels + Off LCD Contrast 6 Levels LCD Backlight 3 Levels + Off LCD backlight mode 0 n/Auto/Off
PoE class Class 1 AC adapter Yes (optional) KX-A423 Installation Poesk stand (Angle) 2 position (30/45) Wall mount Yes (option) Dimension (W x D x H mm) High position: 167 x 165 x 148 (excluding handset) Colour White/ Black Electric Volume Specification 8 Levels SPPhone 8 Levels Handset 8 Levels Ringer 8 Levels + Off LCD Contrast 6 Levels LCD Backlight 3 Levels + Off LCD backlight mode 0 n/Auto/Off
AC adapter Yes (optional) KX-A423 Installation Desk stand (Angle) 2 position (30/45) Wall mount Yes (option) Dimension (W x D x H mm) High position: 167 x 165 x 148 (excluding handset) Colour White/ Black Electric Volume Specification 8 Levels SPPhone 8 Levels Handset 8 Levels - Off Ringer 8 Levels - Off LCD Contrast 6 Levels LCD Backlight 3 Levels - Off LCD backlight mode On/Auto/Off
Installation Desk stand [Angle] 2 position (30/45) Wall mount Yes (option) Dimension [W x D x H mm] High position: 167 x 165 x 148 (excluding handset) Colour White/ Black Electric Volume Specification 8 Levels SPPhone 8 Levels Handset 8 Levels Ringer 8 Levels + Off LCO Contrast 6 Levels LCD Backlight 3 Levels + Off LCD backlight mode 0 n/Auto/Off
Desk stand [Angle] 2 position (30/45) Wall mount Yes (option) Dimension [W x D x H mm] High position: 167 x 165 x 148 (excluding handset) Colour White/ Black Electric Volume Specification 8 Levels SPPhone 8 Levels Handset 8 Levels + Off Ringer 8 Levels + Off LCO contrast 6 Levels LCD Backlight 3 Levels + Off LCD backlight mode On/Auto/Off
Wall mount Yes (option) Dimension (W x D x H mm) High position: 167 x 165 x 148 (excluding handset) Colour White/ Black Electric Volume Specification 8 levels SPPhone 8 levels Handset 8 levels + 0ff LCD Contrast 6 levels LCD Backlight 3 levels + 0ff LCD backlight mode 0 n/Auto/Off
Dimension (W x D x H mm) High position: 167 x 165 x 148 (excluding handset) Colour White/ Black Electric Volume Specification 8 Levels FyPhone 8 Levels Handset 8 Levels Ringer 8 Levels + Off LCD Contrast 6 Levels LCD Backlight 3 Levels + Off LCD backlight mode On/Auto/Off
Colour Low position: 167 x 173 x 115 (excluding handset) Colour White/ Black Electric Volume Specification SPPhone SPPhone 8 levels Handset 8 levels Ringer 8 levels + Off LCD Contrast 6 levels LCD Backlight 3 levels + Off LCD backlight mode On/Auto/Off
Colour White/ Black Electric Volume Specification SPPhone 8 Levels SPPhone 8 Levels 1 Levels Ringer 8 Levels + Off 1 LCD Contrast 6 Levels LCD Backlight 3 Levels + Off 1 LCD Contrast 0 n/Auto/Off
Electric Volume Specification SPPhone 8 Levels Handset 8 Levels Ringer 8 Levels + Off LCD Contrast 6 Levels LCD Backlight 3 Levels + Off LCD backlight mode 0n/Auto/Off
SPPhone 8 Levels Handset 8 Levels Ringer 8 Levels + Off LCD Contrast 6 Levels LCD Backlight 3 Levels + Off LCD backlight mode 0n/Auto/Off
Handset 8 levels Ringer 8 levels + Off LCD Contrast 6 levels LCD Backlight 3 levels + Off LCD backlight mode 0n/Auto/Off
Ringer 8 levels + Off LCD Contrast 6 levels LCD Backlight 3 levels + Off LCD backlight mode 0n/Auto/Off
LCD Contrast 6 Levels LCD Backlight 3 Levels + Off LCD backlight mode On/Auto/Off
LCD Backlight 3 levels + Off LCD backlight mode 0n/Auto/Off
LCD Backlight 3 levels + Off LCD backlight mode 0n/Auto/Off
LCD backlight mode On/Auto/Off
Basic Call Feature
Missed Calls Display Yes
WWay Conference Yes
Busy Lamp field Yes
Call Centre Yes
Call Park Notification Yes
Click to Call Yes
Feature Key Synchronisation Yes
Shared Call Appearance Yes
Broadsoft Xsi Yes
Broadsoft Xsi Yes Broadsoft Presence Yes

